

IN THE CLAIMS

1. (Previously Presented) A method, comprising:

accessing a port of a host system by a satellite system to monitor a parameter for a predetermined event related to the host system;

generating, by a monitoring operations center, a notification upon an occurrence of the predetermined event to a first person in a hierarchy; and

escalating, by the monitoring operations center, the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period.
2. (Original) The method of claim 1, further comprising determining whether the notification is successful.
3. (Original) The method of claim 1, wherein the predetermined event is receipt of a state change of the parameter.
4. (Original) The method of claim 1, wherein the predetermined event is exceeding a threshold value set for the parameter.
5. (Original) The method of claim 1, further comprising generating the notification a number of times for an amount of time.

6. (Original) The method of claim 5, wherein the number of times, the amount of time, and the time period are configurable.
7. (Previously Presented) A method, comprising:
 - monitoring a host system for a parameter corresponding to a predetermined event;
 - generating, by a monitoring operations center, a notification upon an occurrence of the predetermined event to a first person in a hierarchy; and
 - escalating, by the monitoring operations center, the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period, wherein the parameter is monitored using a satellite system located locally to the host system and wherein the notification is generated remotely from the host system.
8. (Canceled)
9. (Original) The method of claim 1, further comprising providing a possible cause of the predetermined event occurrence.
10. (Original) The method of claim 1, where escalation is based on a set of rules.
11. (Original) The method of claim 10, wherein the set of rules is based on a time delay between the notification and the acknowledgement.

12. (Original) The method of claim 10, wherein the set of rules is based on the state change.
13. (Original) The method of claim 10, wherein the set of rules is based on schedules of the first and second persons.
14. (Original) The method of claim 1, wherein the notification is generated and escalated automatically.
15. (Previously Presented) A method, comprising:
monitoring a host system for a parameter corresponding to a predetermined event;
generating, by a monitoring operations center, a notification upon an occurrence of the predetermined event to a first person in the hierarchy;
escalating, by the monitoring operations center, the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period; and
generating, by the monitoring operations center, a trouble ticket at a predetermined point in the hierarchy to track the escalation.
16. (Original) The method of claim 1, wherein the parameter is a service of the host system.

17. (Original) The method of claim 1, wherein the parameter is a utilization of a component of the host system.

18. (Original) The method of claim 17, further comprising:

monitoring additional parameters of the host system, wherein the additional parameters include a service of the host system; and

eliminating a redundant notification based on dependent parameters of the host system.

19. (Previously Presented) A method, comprising:

monitoring a host system for a parameter corresponding to a predetermined event;

generating, by a monitoring operations center, a notification upon an occurrence of the predetermined event to a first person in a hierarchy;

escalating, by the monitoring operations center, the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period; and

determining an asset parameter of the host system.

20. (Previously Presented) A machine readable medium having stored thereon

instructions, which when executed by a processor, cause the processor to perform the following:

receiving an occurrence of a predetermined event related to a host system, the occurrence of the predetermined event determined by access of a port of the host system by a satellite system;

generating, by a monitoring operations center, a notification upon the occurrence of the predetermined event to a first person in a hierarchy; and

escalating, by the monitoring operations center, the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period.

21. (Previously Presented) The machine readable medium of claim 20, wherein the predetermined event is receipt of a state change of the parameter.

22. (Previously Presented) The machine readable medium of claim 20, wherein the processor further performs generating the notification a number of times for an amount of time.

23. (Previously Presented) The machine readable medium of claim 20, wherein the number of times, the amount of time, and the time period are configurable.

24. (Previously Presented) The machine readable medium of claim 20, wherein the processor further performs providing a suggestion as to a cause of the predetermined event occurrence.

25. (Previously Presented) A machine readable medium having stored thereon instructions, which when executed by a processor, cause the processor to perform the following:

- monitoring a host system for a parameter corresponding to a predetermined event;
- generating a notification upon the occurrence of the predetermined event to a first person in a hierarchy; and

- escalating the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period, wherein the processor further performs generating a trouble ticket at a predetermined point in the hierarchy to track the escalation.

26. (Previously Presented) An apparatus, comprising:

- means for monitoring a host system for a parameter corresponding to a predetermined event;

- means for generating a notification upon the occurrence of the predetermined event to a first person in a hierarchy; and

- means for escalating the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period.

27. (Original) The apparatus of claim 26, further comprises means for determining whether the notification is successful.

28. (Original) The apparatus of claims 26, further comprising:

means for generating the notification a number of times for an amount of time.

29. (Previously Presented) An apparatus comprising:

means for monitoring a host system for a parameter corresponding to a predetermined event;

means for generating a notification upon the occurrence of the predetermined event to a first person in a hierarchy;

means for escalating the notification to a second person in the hierarchy when the first person fails to acknowledge the notification in a time period; and

means for generating a trouble ticket at a predetermined point in the hierarchy to track the escalation.

30. (Previously Presented) An apparatus, comprising:

a configuration portal to interface with a satellite system and configure an event for a parameter of a host system;

a digital processing system coupled to the portal, the digital processing system to receive data indicative of an occurrence of the event and generate a first notification; and

a notification gateway coupled to the digital processing system to transmit the first notification to a first communication device, the digital processing system to generate a second notification to a second communication device if an acknowledgment is not received within a predetermined time.

31. (Original) The apparatus of claim 30, wherein the notification gateway transmits the second notification to the second communication device.

32. (Original) The apparatus of claim 30, wherein the digital processing system comprises at least one server.

33. (Original) The apparatus of claim 30, further comprising a proxy server coupled to the digital processing system.

34. (Previously Presented) A system, comprising:

a host satellite system coupled to a first network;

a plurality of communication devices; and

a monitoring operations center coupled to the first network, the monitoring operations center comprising:

a configuration portal to interface with a satellite system and configure an event for a parameter of a host system;

a digital processing system coupled to the portal, the digital processing system to receive data indicative of an occurrence of the event on the first network and generate a first notification; and

a notification gateway coupled to the digital processing system to transmit the first notification to one of the plurality of communication devices, the digital processing system to generate a second notification to another of the plurality of communication devices if an acknowledgment is not received within a predetermined time.

35. (Original) The system of claim 34, wherein the first notification is transmitted on the first network.

36. (Original) The system of claim 34, further comprising a second network and wherein the first notification is transmitted on the second network.

37. (Original) The system of claim 35, wherein the first network is an internet protocol network and the second network is a telephone network.

Claims 38-41 (Not Entered).

42. (Previously Presented) The method of claim 1, wherein generating further comprises transmitting the occurrence of the predetermined event from the satellite system to the monitoring operations center.

43. (Previously Presented) The method of claim 7, wherein the parameter of the host system is monitored by a satellite system, and wherein generating further comprises transmitting the occurrence of the predetermined event from the satellite system to the monitoring operations center to generate the notification.

44. (Previously Presented) The method of claim 15, wherein the parameter of the host system is monitored by a satellite system, and wherein generating the notification

further comprises transmitting the occurrence of the predetermined event from the satellite system to the monitoring operations center.

45. (Previously Presented) The method of claim 20, wherein generating further comprises transmitting the occurrence of the predetermined event from the satellite system to the monitoring operations center.